



Product information RKMCW 4 69543


Name	RKMCW 4
	Field attachable connector, M8 female right angle connector with threaded joint, assembling with solder connections, 4 poles
Delivery informations	
Availability	available
Product description	DVMCIN A
Type	RKMCW 4
Order No. Description	69543 Field attachable connector M9 famale right angle connector with three-ded joint, accompling with colder connections. A pales
Note	Field attachable connector, M8 female right angle connector with threaded joint, assembling with solder connections, 4 poles The application of these products in harsh environments should always be checked before use.
Number of contacts	4
Color of housing	black
Product characteristics	Oil resistance
Classification	Unitestance
Belden brand	Lumberg-Automation
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	angled
Thread	M8
Design of electrical connection	solder connection
Connectable conductor cross-section multiple wire	max. 0.25 mm ²
(without sleeve)	11(A. U.Z.) 11111
LED display present	×
Environmental conditions Conditions	
Environmental temperature	-40 °C 85 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	PBT
Contact bearer material	PA PA
Contact material	CuSn
Contact material - Surface refinement	gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤3 mΩ
Rated current In	4 A at 40°C
Nominal voltage	30 V
Rated voltage	36 V
Test voltage	0.9 kV eff./60 s
Insulation resistance	>1 6Ω

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture

Drawing



*a Kabelverschraubung Screw joint for cable

4-polig 4 poles



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.