

A BELDEN BRAND

Product information Field Attachable M12 Connectors with LED - RKC/LED 4/7 69993

Field Attachable M12 Connectors with LED Name Field attachable connector, M12 female connector, straight version, with threaded joint and LED operation and function indicator, assembling with screw terminals (printed circuit board included) **Delivery informations** Availability available Product description RKC/LED 4/7 Туре Order No 69993 Description Field attachable connector, M12 female connector, straight version, with threaded joint and LED operation and function indicator, assembling with screw terminals (printed circuit board included) Number of contacts 4 Color of housing black Classification Belden brand Lumberg-Automation Eclass-ID 27260702 Mechanical data Type of plug-in contact Female connector Design of housing straight Thread M12 screw connection Design of electrical connection Coding of the M12 round plug connector А LED display present \checkmark Connectable conductor cross-section multiple wire max. 0.75 mm² (without sleeve) Screw joint for cable for external cable diameter 3.0 mm ... 6.5 mm Screwed cable gland, connecting thread SW 15 **Environmental conditions** -25 °C ... 90 °C **Environmental temperature** Degree of protection (IP), mounted IP67 Pollution degree 3 Materials Housing material / Molded body PBT Contact bearer material PBT **Contact material** CuZn Contact material - Surface refinement pre-coppered, CuSnZn Knurled screw / nut material CuZn, nickel-plated FKM Sealing material **Electrical data** Contact resistance $\leq 5 \text{ m}\Omega$ Rated current In 4 A at 40°C, UL and notice derating Rated voltage (Value) 32 V Insulation resistance $> 1 G\Omega$ **Approvals**

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

UL

Approvals