


Product information
RKMVS - RKMVS 4-358/5 M
75022

Name	
Name	RKMVS
	
	Actuator/sensor cordset, single-ended, M8 female connector with self-locking threaded joint and molded cable, shielding connected to knurled nut4 poles, PUR jacket, halogen free, gray, 5 meters.
Delivery informations	
Availability	available
Product description	
Type	RKMVS 4-358/5 M
Order No.	75022
Description	Actuator/sensor cordset, single-ended, M8 female connector with self-locking threaded joint and molded cable, shielding connected to knurled nut4 poles, PUR jacket, halogen free, gray, 5 meters.
Note	The application of these products in harsh environments should always be checked before use.
Number of contacts	4
Color of housing	orange
Product characteristics	Oil resistance, EMC
Classification	
Belden brand	Lumberg-Automation
Mechanical data	
Type of plug-in contact	Female connector
Design of housing	straight
Thread	M8
Design of electrical connection	connector M8
LED display present	✘
Environmental conditions	
Environmental temperature	-30 °C ... 90 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU
Contact bearer material	TPU, fibre-glass reinforced
Contact material	CuZn
Contact material - Surface refinement	gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A at 40°C
Nominal voltage	30 V
Rated voltage	36 V
Test voltage	0.5 kV eff./60 s
Insulation resistance	> 1 GΩ
Approvals	
Approvals	UL
Cable	
Cable length	5 m
Cable number	358


The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.




Cable description	Control cable
Color of jacket	grey
Material of outer jacket	PUR
Without halogens as in EN 50267-2-3	✓
shielded	✗
welding spark proof	✗
Outer diameter of the cable	5.2 mm
Number of conductors	4
Cable design	4 x 0.25 mm ²
Conductor design	32 x 0.10 mm
Flame resistant according to standard	none

[Picture](#)

[Drawing](#)



4-polig
4 poles



*a O-Ring
O-ring
L 1 Abisolierung 30 mm
Stripping 30 mm

1 = braun / brown
2 = weiß / white
3 = blau / blue
4 = schwarz / black