



## Product information RSEM 8 91607


Name	RSEM 8
	THE STATE OF THE S
B	Receptacle connector, M8 male connector for sensors with long solder contacts, solid contacts on solder side and with circumferential collar, 8 poles
Delivery informations	available
Availability Product description	avaliable
Type	RSEM 8
Order No.	91607
Description	Receptacle connector, M8 male connector for sensors with long solder contacts, solid contacts on solder side and with circumferential collar, 8 poles
Note	The application of these products in harsh environments should always be checked before use.
Number of contacts	The application of these products in rialish environments should always be checked before use.  8
Color of housing	without
Product characteristics	Oil resistance
Classification	Un resistance
Belden brand	Lumberg-Automation
Mechanical data	Lutino y Addinatori
Type of plug-in contact	Male connector
Design of housing	straight
Thread	M8
Design of electrical connection	solder connection
LED display present	X
	^ <b>^</b>
Environmental conditions	1.550
Environmental temperature	-25 °C 80 °C
Pollution degree	3
Materials Contact bearer material	PA PA
Contact material - Surface refinement	CuZn
Electrical data	pre-nickeled and 0.8 microns gold-plated
Rated current In	4 A at 40°C
Nominal voltage	32 V
Test voltage	0.8 kV eff./60 s
Insulation resistance	>1 GΩ

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture

Drawing



\*a Einbauöffnung cut out

8-polig 8 poles



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.