




Product information
STAS 3 N grau/grey
932 143-106

| | | |
|-----------------------------------|--|---|
| Name | | STAS 3 N grau/grey |
| | |  |
| | | Cable plug with strain relief |
| Delivery informations | | |
| Availability | | available |
| Product description | | |
| Description | | Cable plug with strain relief |
| Type | | STAS 3 N grau/grey |
| Order No. | | 932 143-106 |
| Type of contact | | male |
| Number of contacts | | 3 + PE |
| Cable gland | | PG 11 |
| Cable diameter | | 6 mm to 10 mm |
| Conductor size | | max. 1.5 mm ² |
| Housing Color | | grey |
| Contact bearer color | | black |
| Technical data | | |
| Pin dimensions | | 2 mm |
| Rated voltage | | AC 400 V / DC 250 V |
| Rated current | | DC 10 A / AC 16 A |
| Contact resistance | | <= 5 mOhm |
| Type of termination | | screw |
| Material | | |
| Contact material | | Cu Zn |
| Contact surface material | | Sn |
| Contact bearer material | | PA |
| Housing material | | PA |
| Environmental conditions | | |
| Protection class (IEC 60529) | | IP 54 |
| Pollution severity | | 3 |
| Temperature range | | -30 °C to +90 °C |
| Inflammability class | | |
| Housing | | UL 94 HB |
| Contact bearer | | UL 94 V-0 |
| Approvals | | |
| UL | | UL |
| VDE | | VDE |
| SEV | | SEV |
| Packing unit | | |
| Packaging unit | | 100 pieces |
| Scope of delivery and accessories | | |
| Accessories to order separately | | safety brackets STASI 3, order no. 732 045-001 |



Picture
Drawing

