




**Product information**  
**STAK 3 K 075 10m**  
**932 187-016**

|                                   |  |  |
|-----------------------------------|--|--|
| Name                              |  | STAK 3 K 075 10m   |
|                                   |  |     |
|                                   |  | Molded-on cable socket with harmonized lead (DIN VDE 0282)                           |
| Delivery informations             |  |  |
| Availability                      |  | available  |
| Product description               |  |  |
| Description                       |  | Molded-on cable socket with harmonized lead (DIN VDE 0282)                           |
| Type                              |  | STAK 3 K 075 10m   |
| Order No.                         |  | 932 187-016  |
| Other standard types              |  | cable length 3,025 m: order no. 932 187-011; cable length 5 m: order no. 932 187-015 |
| Type of contact                   |  | female   |
| Number of contacts                |  | 3 + PE   |
| Cable color                       |  | black  |
| Cable length                      |  | 10 m   |
| Cable diameter                    |  | 7.5 mm   |
| Conductor size                    |  | 0.75 mm <sup>2</sup>   |
| Cable specification               |  | 4 x 0.75 mm <sup>2</sup>   |
| Cable type                        |  | H05 RR-F4G 0,75  |
| Housing Color                     |  | black  |
| Contact bearer color              |  | black  |
| Technical data                    |  |  |
| Pin dimensions                    |  | 2 mm   |
| Rated voltage                     |  | AC 400 V / DC 250 V  |
| Rated current                     |  | DC 10 A / AC 10 A  |
| Contact resistance                |  | <= 5 mOhm  |
| Material                          |  |  |
| Contact material                  |  | Cu Zn  |
| Contact surface material          |  | Sn   |
| Contact bearer material           |  | PA   |
| Housing material                  |  | PA   |
| Environmental conditions          |  |  |
| Protection class (IEC 60529)      |  | IP 54  |
| Pollution severity                |  | 3  |
| Temperature range                 |  | -30°C to +90°C (connector) / -25°C to +60°C (cable)                                  |
| Inflammability class              |  |  |
| Housing                           |  | UL 94 HB   |
| Cable                             |  | VDE 0472 part 804  |
| Contact bearer                    |  | UL 94 V-0  |
| Approvals                         |  |  |
| VDE                               |  | VDE  |
| SEV                               |  | SEV  |
| Packing unit                      |  |  |
| Packaging unit                    |  | 20 pieces  |
| Scope of delivery and accessories |  |  |
| Accessories to order separately   |  | safety brackets STASI 3,<br>order no. 732 045-000                                    |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Picture  
Drawing

