





Product information
N11R AM 2 D M20
934 338-106

Name	
N11R AM 2 D M20	
	
Panel-mounted connector with metal screw-in casing (monoblock design), Stifte flüssigkeitsdicht montiert	
Delivery informations	
Availability	available
Product description	
Description	Panel-mounted connector with metal screw-in casing (monoblock design), Stifte flüssigkeitsdicht montiert
Type	N11R AM 2 D M20
Order No.	934 338-106
Type of contact	male
Number of contacts	11 + PE
Conductor size	max. 0.5 mm ²
Standard	DIN 43651
Housing Color	grey
Technical data	
Pin dimensions	1.6 mm
Rated voltage	AC/DC 60 V
Rated current	5 A
Contact resistance	<= 5 mOhm
Type of termination	solder, concave pins
Suitable cables	0.14 mm ² to 0.5 mm ²
Mounting	M20x1.5
Material	
Contact surface material	Ag
Contact bearer material	PET
Housing material	PET
Environmental conditions	
Protection class (IEC 60529)	IP 65
Temperature range	-40 °C to +90 °C
Packing unit	
Packaging unit	10 pieces
Scope of delivery and accessories	
Scope of delivery	1 panel-mounted connector with O-Ring in polythene bag with assembly instructions
Accessories to order separately	can be plugged into N11R FF, N11R EF; protective cover SHK 2, order no. 733 845-001

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

Picture
Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.