



Product information
RSB switches 8-9 ports, with 1-2 fiber ports -
RSB20-0800S2S2TAABEH
942 014-027

Name		RSB switches 8-9 ports, with 1-2 fiber ports
		
		Ethernet/Fast Ethernet-Switch acc. to IEEE 802.3, compact, managed, Industrial switch for DIN Rail, Store-and-Forward-Switching, fanless design
Delivery informations		
Availability	available	
Product description		
Description	Ethernet/Fast Ethernet-Switch acc. to IEEE 802.3, compact, managed, Industrial switch for DIN Rail, Store-and-Forward-Switching, fanless design	
Port type and quantity	8 ports in total; 1. uplink: 100BASE-FX, SM-SC; 2. uplink: 100BASE-FX, SM-SC; 6 x standard 10/100 BASE TX, RJ45	
Type	RSB20-0800S2S2TAABEH	
Order No.	942 014-027	
More Interfaces		
Power supply/signaling contact	1 x plug-in terminal block, 6-pin	
V.24 interface	1 x RJ11 socket	
Network size - length of cable		
Single mode fiber (SM) 9/125 µm	0-32.5 km, 16 dB link budget at 1300 nm, A=0.4 dB/km, 3 dB reserve, D=3.5 ps/(nm x km)	
Network size - cascading		
Line - / star topology	any	
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0.3 sec.)	
Power requirements		
Operating voltage	24 V DC (18-32 V)	
Current consumption at 24 V DC	315 mA	
Power output in Btu (IT) h	26.2	
Software		
Management	Serial interface, web-interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP	
Diagnostics	LEDs, Log-File, signal contact, RMON (statistic, history, alarms, events), port mirroring, topology discovery 802.1AB	
Configuration	Command Line Interface (CLI), BootP, DHCP, DHCP Option 82, HiDiscovery, auto-configurationadapter (ACA11)	
Security	SNMP V3 (no encryption)	
Redundancy functions	HIPER-Ring (client and server), MRP (client and server), RSTP - IEEE802.1D-2004	
Filter	QoS 4 classes, port prioritisation (IEEE 802.1D/p), multicast IGMP (Snooping and Querier, Fast Aging)	
Industrial Profiles	EtherNet/IP and PROFINET compatible	
Time synchronisation	SNTP Client and Server, IEEE 1588 client	
Flow control	n/a	
Presettings	Standard	
Ambient conditions		
Operating temperature	-40 °C ... 70 °C	
Storage/transport temperature	-40 °C ... 85 °C	
Relative humidity (non-condensing)	10 % ... 95 %	
MTBF	n/a	
Protective paint on PCB	No	
Mechanical construction		
Dimensions (W x H x D)	71 mm x 131 mm x 111 mm	
Mounting	DIN Rail	
Weight	400 g	
Protection class	IP20	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz-150 Hz, 10 cycles, 1 octave/min.
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EN 61000-4-16 mains frequency voltage	n/a
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2 (pending)
Shipbuilding	n/a
Railway norm	n/a
Substation	n/a
Transportation	n/a
Scope of delivery and accessories	
Scope of delivery	Device, terminal block, operating manual

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.