




Product information
Compact OpenRail Gigabit Ethernet Switch
8-24 ports -RS30-2402T1T1SDAEHH08.0.
943 434-037

Name		Compact OpenRail Gigabit Ethernet Switch 8-24 ports
		
		26 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 24 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design
Delivery informations		
Availability	not yet available	
Product description		
Description	26 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 24 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design	
Port type and quantity	26 Ports in total, 2 Gigabit Ethernet ports; 1. uplink: 10/100/1000BASE-TX, RJ45; 2. uplink: 10/100/1000BASE-TX, RJ45; 24 x standard 10/100 BASE TX, RJ45	
Type	RS30-2402T1T1SDAEHH08.0.	
Order No.	943 434-037	
More Interfaces		
Power supply/signaling contact	1 x plug-in terminal block, 6-pin	
V.24 interface	1 x RJ11 socket	
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB	
Network size - length of cable		
Twisted pair (TP)	0 m ... 100 m	
Network size - cascadiability		
Line - / star topology	any	
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0.3 sec.)	
Power requirements		
Operating voltage	12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V (redundant)	
Current consumption at 24 V DC	654 mA	
Current consumption at 48 V DC	327 mA	
Power output in Btu (IT) h	53.6	
Software		
Management	Serial interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP	
Diagnostics	LEDs, log-file, relay contact, RMON, port mirroring 1:1, topology discovery 802.1AB, address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (μ W and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning.	
Configuration	Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic invalid configuration undo, configuration signature (water marking)	
Security	Port Security (IP und MAC) with multiple addresses, SNMP V3 (no encryption)	
Redundancy functions	HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, MRP and RSTP in parallel, redundant 24 V power supply	
Filter	QoS 4 classes, port prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, multicast (IGMP Snooping/Querier), multicast detection unknown multicast, broadcastlimiter, fast aging	
Industrial Profiles	EtherNet/IP and PROFINET (2.2 PDEV, GSDML stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix	
Time synchronisation	SNTP client/server, PTP / IEEE 1588	
Flow control	Flow control 802.3x, port priority 802.1D/p, priority (TOS/DIFFSERV)	
Presettings	Standard	
Ambient conditions		
Operating temperature	0 °C ... 60 °C	
Storage/transport temperature	-40 °C ... 70 °C	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Relative humidity (non-condensing)		10 % ... 95 %
MTBF		33.5 years (MIL-HDBK-217F)
Protective paint on PCB		No
Mechanical construction		
Dimensions (W x H x D)		110 mm x 131 mm x 111 mm
Mounting		DIN Rail
Weight		600 g
Protection class		IP20
Mechanical stability		
IEC 60068-2-27 shock		15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration		1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity		
EN 61000-4-2 electrostatic discharge (ESD)		6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field		10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)		2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage		power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity		3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EMC emitted immunity		
FCC CFR47 Part 15		FCC 47 CFR Part 15 Class A
EN 55022		EN 55022 Class A
Approvals		
Safety of industrial control equipment		cUL 508
Hazardous locations		ISA 12.12.01 Class 1 Div. 2
Shipbuilding		n/a
Railway norm		n/a
Substation		n/a
Scope of delivery and accessories		
Scope of delivery		Device, terminal block, operating manual

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.