



Product information

RPS 30

943 662-003

Name	
RPS 30	
	
24 V DC DIN rail power supply unit	
Delivery informations	
Availability	available
Product description	
Description	24 V DC DIN rail power supply unit
Type	RPS 30
Order No.	943 662-003
More Interfaces	
Voltage input	1 terminal block, 3-pin
Voltage output	1 terminal block, 5-pin
Power requirements	
Operating voltage	230 V
Input data	
230 V	100 to 240 V AC; 47 to 63 Hz or 85 to 375 V DC
Current consumption	
230 V	max. 0,35 A at 296 V AC
Activation current	< 36 A at 240 V AC and cold start
Output data	
Output voltage	24 V DC (-0,5%, +0,5%)
Output current	
230 V	1,3 A at 100 - 240 V AC
Service	
Diagnostics	LED (power, DC ON)
Redundancy	
Redundancy functions	Power supply units can be connected in parallel
Ambient conditions	
Operating temperature	-10 °C to +70 °C (from 60 °C derating)
Storage/transport temperature	-25 °C to +85 °C
Relative humidity (non-condensing)	max. 95% without condensation
MTBF	74.2 years; Siemensnorm SN 29500 : 40 °C
Mechanical construction	
Dimensions (W x H x D)	45 mm x 75 mm x 98 mm
Mounting	DIN Rail 35 mm
Weight	230 g
Protection class	IP 20
EMC interference immunity	
EN 50082-1	EN 61000-6-2 (includes EN 55024)
EN 50082-2	EN 61000-6-2 (includes EN 55024)
EMC emitted immunity	
EN 50081-1	EN 50081-1
EN 50081-2	EN 50081-2
Approvals	
Safety of industrial control equipment	cUL 508
Safety of information technology equipment	cUL 60950-1

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Hazardous locations	
	ISA 12.12.01 Class 1 Div. 2 (pending)
Shipbuilding	
	Germanischer Lloyd
Scope of delivery and accessories	
Scope of delivery	
	Rail power supply, Description and operating manual

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.