



Product information
SPIDER 4TX/1FX-SM EEC
943 880-001

Name		SPIDER 4TX/1FX-SM EEC
		
		Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)
Delivery informations		
Availability	available	
Product description		
Description	Entry Level Industrial ETHERNET Rail Switch, store and forward switching mode, Ethernet and Fast-Ethernet (10/100 Mbit/s)	
Port type and quantity	4 x 10/100BASE-TX, TP cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity 1 x 100BASE-FX, SM cable, SC sockets	
Type	SPIDER 4TX/1FX-SM EEC	
Order No.	943 880-001	
More Interfaces		
Power supply/signaling contact	1 plug-in terminal block, 3-pin, no signaling contact	
Network size - length of cable		
Twisted pair (TP)	0 - 100 m	
Single mode fiber (SM) 9/125 µm	0 - 32,5 km, 16 dB Link Budget at 1300 nm, A = 0,4 dB/km, 3 dB Reserve, D = 3,5 ps/(nm x km)	
Network size - cascability		
Line - / star topology	Any	
Power requirements		
Operating voltage	9,6 V DC - 32 V DC	
Current consumption at 24 V DC	Max. 150 mA	
Power consumption	Max. 3,9 W 13,3 Btu (IT)/h at 24 V DC	
Service		
Diagnostics	LEDs (power, link status, data, data rate)	
Ambient conditions		
Operating temperature	-40 °C to +70 °C	
Storage/transport temperature	-40 °C to +70 °C	
Relative humidity (non-condensing)	10% to 95%	
MTBF	93,9 years; MIL-HDBK 217F; Gb 25 °C	
Mechanical construction		
Dimensions (W x H x D)	25 mm x 114 mm x 79 mm	
Mounting	DIN Rail 35 mm	
Weight	120 g	
Protection class	IP 30	
Mechanical stability		
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks	
IEC 60068-2-6 vibration	3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.	
EMC interference immunity		
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge	
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)	
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line	
EN 61000-4-5 surge voltage	Power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line	
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 kHz)	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



EMC emitted immunity

FCC CFR47 Part 15 FCC CFR47 Part 15 Class A

EN 55022 EN 55022 Class A

Approvals

Safety of industrial control equipment cUL 508

Scope of delivery and accessories

Scope of delivery Device, terminal block, operating manual

Accessories to order separately Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.