




Product information
SPIDER II 8TX/2FX-ST EEC
943 958-221

Name		SPIDER II 8TX/2FX-ST EEC
		
		Entry Level Industrial ETHERNET Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
Delivery informations		
Availability		available
Product description		
Description		Entry Level Industrial ETHERNET Rail-Switch, store and forward switching mode, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)
Port type and quantity		8 x 10/100BASE-TX, TP-cable, RJ45 sockets, auto-crossing, auto-negotiation, auto-polarity, 2 x 100BASE-FX, MM-cable, ST sockets
Type		SPIDER II 8TX/2FX-ST EEC
Order No.		943 958-221
More Interfaces		
Power supply/signaling contact		1 plug-in terminal block, 3-pin, no signaling contact
Network size - length of cable		
Twisted pair (TP)		0 - 100 m
Multimode fiber (MM) 50/125 µm		0 - 5000 m, 8 dB link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm		0 - 4000 m, 11 dB link budget bei 1300 nm, A = 1 dB/km, 3 dB reserve, B = 500 MHz x km
Single mode fiber (SM) 9/125 µm		n/a
Single mode fiber (LH) 9/125 µm (long haul transceiver)		n/a
Network size - cascability		
Line - / star topology		Any
Power requirements		
Operating voltage		DC 9.6 V - 32 V
Current consumption at 24 V DC		max. 330 mA
Power consumption		max. 8.4 W 28.7 Btu(IT)/h
Service		
Diagnostics		LEDs (power, link status, data, data rate)
Redundancy		
Redundancy functions		n/a
Ambient conditions		
Operating temperature		-40 °C to +70 °C
Storage/transport temperature		-40 °C to +85 °C
Relative humidity (non-condensing)		10% to 95%
MTBF		55.2 years MIL-HDBK 217F: Gb 25°C
Mechanical construction		
Dimensions (W x H x D)		35 mm x 138mm x 121 mm
Mounting		DIN Rail 35 mm
Weight		260 g
Protection class		IP 30
Mechanical stability		
IEC 60068-2-27 shock		15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration		3,5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz - 80 kHz)

EMC emitted immunity

FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A

Approvals

Safety of industrial control equipment	cUL 508
EMV regulations for assembly in vehicles	n/a
Employment in vehicles	E1

Scope of delivery and accessories

Scope of delivery	Device, terminal block, operating manual
Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame