




Product information
M-SFP-BIDI-Bundle LX/LC EEC
943 974-101

Name	
M-SFP-BIDI-Bundle LX/LC EEC	
	
SFP Fiberoptic bi-directional Gigabit Ethernet Transceiver SM, single strand, bundle = 1 x type A and 1 x type B	
Delivery informations	
Availability	available
Product description	
Description	SFP Fiberoptic bi-directional Gigabit Ethernet Transceiver SM, single strand, bundle = 1 x type A and 1 x type B
Port type and quantity	1 x 1000BASE-LX with LC connector, extended temperature range
Type	M-SFP-BIDI-Bundle LX/LC EEC
Order No.	943 974-101
Network size - length of cable	
Multimode fiber (MM) 50/125 µm	n/a
Multimode fiber (MM) 62.5/125 µm	n/a
Single mode fiber (SM) 9/125 µm	0 m - 20 km, 0 - 11 dB Link Budget (1310nm type A, 1550 nm type B) A = 0.4 dB/km, 3 dB Reserve, D = 3.5 ps / (nm x km)
Single mode fiber (LH) 9/125 µm (long haul transceiver)	n/a
Power requirements	
Operating voltage	power supply via the switch
Power consumption	1 W
Service	
Diagnostics	optical input and output power, transceiver temperature
Ambient conditions	
Operating temperature	-40 °C to +85 °C
Storage/transport temperature	-40°C to +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	n/a
Mechanical construction	
Dimensions (W x H x D)	20 mm x 18 mm x 50 mm
Mounting	SFP slot
Weight	40 g
Protection class	IP 20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Scope of delivery and accessories

Scope of delivery	SFP module
Accessories to order separately	n/a

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.