

KEL 16-2MT

Extended cable entry frames



V2A anti-corrosive




Also available with stainless steel screws (V2A).



Also available with threaded bushings.



1.11

| Description | Type | Order No. | Grommets small large | PU |
|---|-------------------------------|-----------|------------------------|----|
|  | KEL 16 24-2MT | 42149 | 24 - | 1 |
| | KEL 16 24-2MT with V2A screws | 42149.200 | 24 - | 1 |
|  | KEL 16 12-2MT | 42148 | 8 4 | 1 |
| | KEL 16 12-2MT with V2A screws | 42148.200 | 8 4 | 1 |
|  | KEL 16 6-2MT | 42147 | - 6 | 1 |
| | KEL 16 6-2MT with V2A screws | 42147.200 | - 6 | 1 |

Product description

The KEL 16-2MT is our largest frame providing the ability to route and seal up to 96 cables.

The cable entry frames KEL 16-2MT series are KEL 16 frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 96 cables. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

| | |
|--------------------|--|
| Material | Polyamide (PA) |
| Flame class | UL94-Vo, self-extinguishing |
| IP rating | IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529) |
| Temperature | -40°C to + 140°C (static) |
| Properties | Halogen-free, silicone-free |
| Cut-out dimensions | 126 × 86 mm |
| Frame depth | 17 mm |

Accessories

| | |
|--------------------------|-----------|
| Cable grommets | 48 - 52 |
| KEL-EMC Cable collectors | 138 - 140 |
| ST Plugs | 53 |