

# KEL 16-E

## Extended cable entry frames



V2A anti-corrosive

Also available with stainless steel screws (V2A).





Also available with threaded bushings.



**IP54**

1.11

Description	Type	Order No.	Grommets small   large	PU
	KEL 16 12-E	42141	12 -	1
	KEL 16 12-E with V2A screws	42141.200	12 -	1
	KEL 16 6-E	42140	4 2	1
	KEL 16 6-E with V2A screws	42140.200	4 2	1

### Product description

The cable entry frame KEL 16-E offers a larger frame size for routing a greater amount of cables, pipes or conduits.

The KEL16-E series are KEL 16 frames extended with an additional middle frame for routing additional cables. Thus allowing a quick, easy and cost effective routing solution for up to 48 cables.

A flat rubber gasket is included in the shipment.

### Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

### Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of cable grommets (certified acc. to EN 60529)
Temperature Properties	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	66 × 86 mm
Frame depth	17 mm

### Accessories

Cable grommets	48 - 52
KEL-EMC Cable collectors	138 - 140
ST Plugs	53