KEL-DPZ-B

Cable entry plates

IP66

Also available in black.

Also available with threaded bushings.

Membrane on front

Product description

The KEL-DPZ-B entry plates are designed for routing cables without connectors.

The assembly of the KEL-DPZ-B with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane and push the cables through. The KEL-DPZ-B provides strain relief and protection IP66 / UL type 12.

With an area of only 46 × 46 mm, up to 25 cables can be easily routed and sealed.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Advantages & benefits

- Space saving shape
- Dual sealing of cables acc. to IP66/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

Specifications

Material	**Frame: Polyamide (PA)** **Sealing plate: Elastomer**
Colour	**grey (similar RAL 7035)** **black**
Flame class	**UL94-V0, self-extinguishing**
IP rating	**IP66 (certified acc. to EN 60529)**
UL type rating	**UL type 12 (acc. to UL 50E)**
Temperature	**- 40°C to + 90°C (static)**
Properties	**Halogen-free, silicone-free**
Cut-out dimensions	**46 × 46 mm / page 218 - 219**
Plate depth	**10 mm**

Accessories

ST-B Plugs	85
FP Flanged plates	178 - 183

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-B 13	43794 50794	8× 3.2 - 6.5 mm 4× 5 - 10.2 mm 1× 16 - 22 mm	10
	KEL-DPZ-B 17	43796 50796	10× 3.2 - 6.5 mm 4× 5 - 10.2 mm 2× 7.5 - 12 mm 1× 9 - 16.2 mm	10
	KEL-DPZ-B 25	43798 50798	25x 3.2 - 6.5 mm	10

* Only valid for grey product types