

KEL-DPZ-KL

Cable entry plates



IP65



Also available in black.



Membrane on front



Conical shape on back provides additional sealing and strain relief

Product description

The cable entry plate KEL-DPZ-KL is designed for routing up to 72 cables without connectors.

The assembly of the KEL-DPZ-KL with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-KL provides strain relief and protection IP65 / UL type 12.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

The KEL-DPZ-KL matches on terminal boxes KL by Rittal.

Advantages & benefits

- Space saving shape
- Dual sealing of cables acc. to IP65/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

Specifications

Material	Frame: Stainless steel V2A, moulded with elastomer Sealing plate: Elastomer Screws: Stainless steel V2A
Colour	■ grey (similar RAL 7035) ■ black
Flame class	UL94-Vo, self-extinguishing
IP rating	IP65 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	192 × 62 mm
Plate depth	4 mm

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-KL 72	■ 43675.001 ■ 43675.101	42× 3.2 - 6.5 mm 21× 5 - 10.2 mm 6× 9 - 16.2 mm 3× 16 - 22 mm	1

* Only valid for grey product types

Accessories

ST-B Plugs 85