


# KT-DPF | KTMB

## Grommets, multi-range



KT-DPF / KTMB small



KT-DPF-B



1.1

Description	Type	Order No.	Size KT	Clamping range	PU
 KT-DPF-A	■ 41260 ■ 41360	41260	KT small	3 - 12 mm	10
		41360			
 KT-DPF-B	■ 41261 ■ 41361	41261	KT large	4 - 18 mm	10
		41361			
 KT-DPF-C	■ 41262 ■ 41362	41262	KT large	14 - 26 mm	10
		41362			
 KTMB-D   Cross section KTMB		41432	KT small	2.5 - 6.5 mm	10
		41434	KT small	4 - 7.5 mm	10
		41436	KT small	6.5 - 10 mm	10
		41438	KT small	9.5 - 13 mm	10
		41440	KT small	13 - 16 mm	10
 KTMB-I		41460	KT large	13 - 18 mm	10
		41465	KT large	18 - 23 mm	10
		41470	KT large	23 - 28 mm	10
		41475	KT large	28 - 33 mm	10
 KTMB-K		41480	KT large	2x 13 - 18 mm	10

### Product description

The KT-DPF / KTMB grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. The KTMB grommets are not split and therefore only usable for cables without connectors. Cutting of KT-DPF grommets: Cable diameter less 20%.

### ■ Specifications grey

Material	Elastomer
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 90°C (static)
Properties	Halogen-free, silicone-free

### ■ Specifications black

Material	Elastomer
Flame class	UL94-HB
IP rating	IP54
Temperature	- 30°C to + 90°C (static)
Properties	Higher chemical resistance

### KMS Cable template

The correct size of the KT grommets can easily be determined by using the stainless steel cable template.

- Determining the diameter of the cable using the cable template
- Selecting the KT grommets according to the data on the cable template

Order No. 39800



\*Only valid for grey product types