



<b>DATA SHEET</b>	0151001
<b>DIN extension cable KE 1 L 2x1,5</b>	valid from : 01.12.2008

## Application

The extension cable KE 1 L 2 x 1,5 mm<sup>2</sup> are PVC insulated cores which transmit the thermoelectric voltage of Fe/CuNi thermocouples. They are for fixed installation in dry and damp rooms and may only be installed outdoors with mechanical and UV protection and in observation of the max. permitted temperature range.

## Design

Conductor	1,5 mm <sup>2</sup> (48 x 0,20 mm)
Conductor material	LX alloying, accuracy class 2 according DIN 43722 Positive conductor: Fe (iron) Negative conductor: CuNi (cupronickel)
Core insulation	PVC compound
Core identification	Positive conductor: red Negative conductor: blue
Core layering	Cores twisted together
Outer sheath	No outer sheath

## Electrical properties

Limiting deviation class 2      ± 140 µV (± 2,5 °C) / m measuring point temperature +500 °C

## Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	12 x cable diameter

Originator: Frank Hörtnagl / PD-KL Approved: Werner Körner / TE	Document: DB0151001EN	page 1 of 1
--	-----------------------	-------------