

## H05Z-K 90 °C

Harmonised; halogen-free to protect human life, the environment and material assets

H05Z-K 90 °C, &lt;  
HAR&gt;  
, Halogen-free single core, harmonised, for wiring in control cabinets, nominal voltage 300/500V

### Info

CPR: Article number choice under [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)  
Halogen-free and harmonised (HAR)  
For expanded ambient temperatures  
see ÖLFLEX® HEAT 125 SC



Halogen-free

### Benefits

Protection of human life and the environment thanks to the avoidance of the formation of acid in case of fire  
Time-saving assembly

### Application range

For wiring of lamps, devices, switchgear cabinets and distribution boxes  
For installation in tubes, on, in and under plaster as well as in closed installation ducts  
In building with a high density of people or valuable assets  
For use in dry rooms  
For expanded ambient temperatures  
see ÖLFLEX® HEAT 125 SC

### Product features

The insulation material is halogen-free and free of other materials which could release toxic gases in the event of fire  
Low amount of corrosive gases in the event of fire  
Low smokes/low smoke density in the event of fire according to IEC 61034  
Flame-retardant according IEC 60332-1-2

Last Update (04.08.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## H05Z-K 90 °C

### Norm references / Approvals

<HAR> cable type certification acc. EN 50525-3-41

### Product Make-up

Fine-wire strand made of bare copper wires

Core insulation: Halogen-free

### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000993

ETIM 5.0 Class-Description: Single core cable

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000993

ETIM 6.0 Class-Description: Single core cable

Conductor stranding:

Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5

Minimum bending radius:

According to EN 50565-1

4 x outer diameter (OD) for normal use; 2 x OD for cautious bending

Nominal voltage:

U0/U: 300/500 V

Test voltage:

2000 V AC

Current rating:

VDE 0298-4

EN 50565-1/ VDE 0298-565-1

Temperature range:

During installation: -5 °C bis +90 °C

Fixed installation: -40 °C bis +90 °C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Packaging size: Coil ≤ 30 kg, otherwise drum

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**H05Z-K 90°C**

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	Core colour	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)
4725001	0.5	2.1 - 2.6	green/yellow	100	-	4.8	9
4725001K	0.5	2.1 - 2.6	green/yellow	-	3000	4.8	9
4725121	0.5	2.1 - 2.6	green	100	-	4.8	9
4725121K	0.5	2.1 - 2.6	green	-	3000	4.8	9
4725031	0.5	2.1 - 2.6	brown	100	-	4.8	9
4725031K	0.5	2.1 - 2.6	brown	-	3000	4.8	9
4725011	0.5	2.1 - 2.6	black	100	-	4.8	9
4725011K	0.5	2.1 - 2.6	black	-	3000	4.8	9
4725061	0.5	2.1 - 2.6	grey	100	-	4.8	9
4725061K	0.5	2.1 - 2.6	grey	-	3000	4.8	9
4725021	0.5	2.1 - 2.6	blue	100	-	4.8	9
4725021K	0.5	2.1 - 2.6	blue	-	3000	4.8	9
4725141	0.5	2.1 - 2.6	dark blue	100	-	4.8	9
4725141K	0.5	2.1 - 2.6	dark blue	-	3000	4.8	9
4725091	0.5	2.1 - 2.6	orange	100	-	4.8	9
4725091K	0.5	2.1 - 2.6	orange	-	3000	4.8	9
4725071	0.5	2.1 - 2.6	violet	100	-	4.8	9
4725071K	0.5	2.1 - 2.6	violet	-	3000	4.8	9
4725111	0.5	2.1 - 2.6	yellow	100	-	4.8	9
4725111K	0.5	2.1 - 2.6	yellow	-	3000	4.8	9
4725051	0.5	2.1 - 2.6	white	100	-	4.8	9
4725051K	0.5	2.1 - 2.6	white	-	3000	4.8	9
4725041	0.5	2.1 - 2.6	red	100	-	4.8	9
4725041K	0.5	2.1 - 2.6	red	-	3000	4.8	9
4725081	0.5	2.1 - 2.6	pink	100	-	4.8	9
4725081K	0.5	2.1 - 2.6	pink	-	3000	4.8	9
4725002	0.75	2.2 - 2.8	green/yellow	100	-	7.2	11
4725002K	0.75	2.2 - 2.8	green/yellow	-	2500	7.2	11
4725122	0.75	2.2 - 2.8	green	100	-	7.2	11
4725122K	0.75	2.2 - 2.8	green	-	2500	7.2	11
4725032	0.75	2.2 - 2.8	brown	100	-	7.2	11
4725032K	0.75	2.2 - 2.8	brown	-	2500	7.2	11
4725012	0.75	2.2 - 2.8	black	100	-	7.2	11
4725012K	0.75	2.2 - 2.8	black	-	2500	7.2	11

**H05Z-K 90°C**

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	Core colour	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)
4725062	0.75	2.2 - 2.8	grey	100	-	7.2	11
4725062K	0.75	2.2 - 2.8	grey	-	2500	7.2	11
4725022	0.75	2.2 - 2.8	blue	100	-	7.2	11
4725022K	0.75	2.2 - 2.8	blue	-	2500	7.2	11
4725142	0.75	2.2 - 2.8	dark blue	100	-	7.2	11
4725142K	0.75	2.1 - 2.8	dark blue	-	2500	7.2	11
4725092	0.75	2.1 - 2.8	orange	100	-	7.2	11
4725092K	0.75	2.1 - 2.8	orange	-	2500	7.2	11
4725072	0.75	2.2 - 2.8	violet	100	-	7.2	11
4725072K	0.75	2.2 - 2.8	violet	-	2500	7.2	11
4725112	0.75	2.2 - 2.8	yellow	100	-	7.2	11
4725112K	0.75	2.2 - 2.8	yellow	-	2500	7.2	11
4725052	0.75	2.2 - 2.8	white	100	-	7.2	11
4725052K	0.75	2.2 - 2.8	white	-	2500	7.2	11
4725042	0.75	2.2 - 2.8	red	100	-	7.2	11
4725042K	0.75	2.2 - 2.8	red	-	2500	7.2	11
4725082	0.75	2.2 - 2.8	pink	100	-	7.2	11
4725082K	0.75	2.2 - 2.8	pink	-	2500	7.2	11
4725003	1	2.4 - 2.9	green/yellow	100	-	9.6	14
4725003K	1	2.4 - 2.9	green/yellow	-	2000	9.6	14
4725123	1	2.4 - 2.9	green	100	-	9.6	14
4725123K	1	2.4 - 2.9	green	-	2000	9.6	14
4725033	1	2.4 - 2.9	brown	100	-	9.6	14
4725033K	1	2.4 - 2.9	brown	-	2000	9.6	14
4725013	1	2.4 - 2.9	black	100	-	9.6	14
4725013K	1	2.4 - 2.9	black	-	2000	9.6	14
4725063	1	2.4 - 2.9	grey	100	-	9.6	14
4725063K	1	2.4 - 2.9	grey	-	2000	9.6	14
4725023	1	2.4 - 2.9	blue	100	-	9.6	14
4725023K	1	2.4 - 2.9	blue	-	2000	9.6	14
4725143	1	2.4 - 2.9	dark blue	100	-	9.6	14
4725143K	1	2.4 - 2.9	dark blue	-	2000	9.6	14
4725093	1	2.4 - 2.9	orange	100	-	9.6	14
4725093K	1	2.4 - 2.9	orange	-	2000	9.6	14

## H05Z-K 90°C

Article number	Conductor cross-section (mm <sup>2</sup> )	Outer diameter [mm]	Core colour	m/ring	m/box	Copper index (kg/km)	Weight (kg/km)
4725073	1	2.4 - 2.9	violet	100	-	9.6	14
4725073K	1	2.4 - 2.9	violet	-	2000	9.6	14
4725113	1	2.4 - 2.9	yellow	100	-	9.6	14
4725113K	1	2.4 - 2.9	yellow	-	2000	9.6	14
4725053	1	2.4 - 2.9	white	100	-	9.6	14
4725053K	1	2.4 - 2.9	white	-	2000	9.6	14
4725043	1	2.4 - 2.9	red	100	-	9.6	14
4725043K	1	2.4 - 2.9	red	-	2000	9.6	14
4725083	1	2.4 - 2.9	pink	100	-	9.6	14
4725083K	1	2.4 - 2.9	pink	-	2000	9.6	14
4725263K	1	2.4 - 2.9	blue/white	-	2000	9.6	14

Last Update (04.08.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16

**H05Z-K 90°C**