

ÖLFLEX® CRANE F

Weather-resistant flat rubber cables

ÖLFLEX® CRANE F - Flat cable for outdoor use and crane applications/conveyour technology. Power and control rubber cable, U₀/U:300/500V

Info

For outdoor cable trolley application

Space-saving installation

Also suitable for power chains and lift applications



UV-resistant



Oil-resistant



Suitable for outdoor use



Cold-resistant

Benefits

Weather-resistant for harsh environmental conditions

Flat cables need less space than round cables

Smaller bending radii is possible

Last Update (28.12.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® CRANE F

Application range

As a lift control cable: max. 50 m suspension length

In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems

Sewage treatment plants, steelworks and high rack facilities

The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

Product features

Flame-retardant according IEC 60332-1-2

Norm references / Approvals

Based on VDE 0250-809 (NGFLGÖU)

Product Make-up

Strands of bare or tinned-copper wires

Core insulation: rubber compound

Outer sheath: special rubber compound

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000825

ETIM 5.0 Class-Description: Flat cable

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000825

ETIM 6.0 Class-Description: Flat cable

Core identification code:

Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9

From 6 cores: black with white numbers

Conductor stranding:

Copper conductor according to VDE 0295/IEC 60228
up to 25 mm²: extra-fine wire, class 6
from 35 mm²: fine wire, class 5

Minimum bending radius:

Flexible use: 10 x cable thickness

Fixed installation: 4 x cable thickness

Nominal voltage:

U0/U: 300/500 V

Test voltage:

3000 V

Protective conductor:

G = with GN-YE protective conductor

X = without protective conductor

Temperature range:

Flexible use: -25 °C to +90 °C

Fixed installation: -40 °C to +90 °C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



LAPP GROUP

PRODUCT INFORMATION

ÖLFLEX® CRANE F

Article number	Number of cores and mm ² per conductor	Outer dimensions, width x height (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE F				
0041041	4.0 G 1.5	17.5 x 6.2	57.6	200
0041042	5.0 G 1.5	21.5 x 6.2	72	240
0041043	7.0 G 1.5	29 x 6.2	100.8	360
0041044	8.0 G 1.5	31.5 x 6.2	115	370
0041045	10.0 G 1.5	40 x 6.5	144	520
0041046	12.0 G 1.5	47 x 6.5	172.8	620
0041047	4.0 G 2.5	21 x 7.5	96	280
0041048	5.0 G 2.5	27 x 7.5	120	400
0041049	7.0 G 2.5	35 x 7.5	168	520
0041050	8.0 G 2.5	39 x 7.5	192	550
0041051	12.0 G 2.5	56 x 8	288	800
0041052	4.0 G 4	26 x 9	153.6	410
0041053	7.0 G 4	42 x 9	268.8	700
0041054	4.0 G 6	29 x 9.5	230	600
0041055	5.0 G 6	35 x 9.5	288	650
0041056	7.0 G 6	42 x 9.5	403	850
0041057	4.0 G 10	33 x 11	384	800
0041059	4.0 G 16	38 x 13	614	1150
0041060	4.0 G 25	49.5 x 15	960	1700
0041061	4.0 G 35	55 x 17	1344	2360
0041062	4.0 G 50	63 x 19	1920	3000
0041063	4.0 G 70	71 x 22	2688	4000

Last Update (28.12.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16