

HITRONIC® PCF cables for PROFINET Applications

Polymer optical fibre as duplex fibre cable version with PCV or PUR sheath for PROFINET applications type B or C

PROFINET compliant optical cables accordingly Type B and Type C with 2K200/230 PCF twin cable, colour coded J-VY(ZN)Y, AT-V(ZN)Y(ZN)11Y

Info

PROFINET compliant

- Type B or Type C

For direct connector assembly



Power chain



Optimum strain relief



Low weight



Heat-resistant



Mechanical and plant engineering



Kompletterande automationskomponenter från Lapp

Benefits

Optical data transmission up to 500m

Easy to handle

No interference by external fields

No grounding problems

Suitable for direct connector assembly

Last Update (25.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

HITRONIC® PCF cables for PROFINET Applications

Application range

PCF DUPLEX cables for optical signal transmission in industrial applications

PROFINET / Industrial Ethernet

At 100 Mbit/s: max 100 m cable length

PROFINET type B:

for fixed laying

PROFINET type C:

for flexible applications (power chains)

Product features

Cable version with PVC outer sheath:

for standard applications in industrial environments

Cable version with PUR outer sheath:

for high mechanical or chemical stress in industrial environments

PNB - PROFINET-Type B

PNC - PROFINET-Type C

FD - Highly flexible (power chains)

Norm references / Approvals

28055702: with c(UL)us certification

(OFNG 75°C)

Product Make-up

Colour-coded, tight-buffered PCF sub-cable with PVC sheath

Sub cable outer diameter: 2.2mm

Aramid yarns as strain relief

Outer sheath material PUR or PVC (see article description)

Outer sheath colour: green (RAL 6018)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000034 ETIM 5.0 Class-Description: Fibre optic cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000034 ETIM 6.0 Class-Description: Fibre optic cable
Dimensions:	Buffered fibre: 0.5mm Single cable: 2.2 mm Cable: see table
Core identification code:	Black, orange (with arrow printing)
Fibre type:	PCF - K200/230 PCF - Polymer Cladded Fibre
Minimum bending radius:	see data sheet
Standard designation:	J-V(ZN)YY 2K200/230 J-V(ZN)Y(ZN)11Y 2K200/230 flex J-V(ZN)Y(ZN)Y 2K200/230 flex
Optical fibre type:	Core material: glass Cladding material: fluoropolymers
Permissible tensile force:	see data sheet
Temperature range:	See data sheet

Last Update (25.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

HITRONIC® PCF cables for PROFINET Applications

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

The cables can also be supplied as pre-terminated fibre optic trunks.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

HITRONIC® PCF cables for PROFINET Applications

Article number	Article designation	Fibre type	Number of fibres	Outer diameter [mm]	Weight (kg/km)
PCF DUPLEX - PROFINET TYPE B					
28055702	HITRONIC® PCF DUPLEX PNB PVC-PVC A	200/230 PCF	2	7.5	59
28052702	HITRONIC® PCF DUPLEX PNB PVC-PVC	200/230 PCF	2	7.2	55
PCF DUPLEX - PROFINET TYPE C					
28351702	HITRONIC® PCF DUPLEX FD PNC PVC-PUR	200/230 PCF	2	8.8	71
28352702	HITRONIC® PCF DUPLEX FD PNC PVC-PVC	200/230 PCF	2	8.8	76

Last Update (25.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

HITRONIC® PCF cables for PROFINET Applications