

## ÖLFLEX® CHARGE

VDE EVC cable to charge electrically powered vehicles and for spiralization

ÖLFLEX® CHARGE: EVC/ VDE-AR-E 2283-5, Power and control/ electromobile/ charge column load charging cable, halogen-free, flame retardant, outdoor, spiralizable

### Info

VDE EVC type certified

Halogen-free and flame-retardant

Spiralizable

LAPP KABEL STUTTGART ÖLFLEX® CHARGE EVC 306+0,5 450/750 VAC VDE-Reg. 8727 R4H0 CC



UV-resistant



Acid-resistant



Oil-resistant



Mechanical resistance



Halogen-free



Good chemical resistance



e-Mobility



Suitable for outdoor use

Last Update (29.06.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® CHARGE



Cold-resistant

### Benefits

Charging process IEC 61851-1  
 Low toxicity of flue in the event of fire  
 Suitable for spiralization, except for 5G6mm<sup>2</sup>+1X0.5mm<sup>2</sup>

### Product features

Flame-retardant acc. IEC 60332-1-2 as well as Halogen-free acc. VDE-AR-E 2283-5/ appendices B+C, EN 50267-2-1, EN 50267-2-2, EN 50525-1/ appendix C, EN 60684-2  
 UV-resistant acc. EN ISO 4892-2, 2.4.20, as well as ozone-resistant acc. EN 50396, 8.1.3, for outdoor use  
 Cold-flexible as well as water-resistant according to AD6 of HD 516 and VDE-AR-E 2283-5, appendix I  
 Resistance to acids and solutions according to EN 60811  
 High resistance to usual vehicle chemicals according to VDE-AR-E 2283-5, appendix G

### Norm references / Approvals

<VDE> EVC cable type registration issued by the VDE according to the VDE application rule VDE-AR-E 2283-5

### Product Make-up

Finely stranded, bare copper conductors of IEC conductor class 5 acc. IEC 60228  
 Core insulations of power cores made of special, halogen-free, cross-linked elastomer EVI-2 acc. VDE-AR-E 2283-5  
 Core insulation control/ pilot core(s): Halogen-free, thermoplastic, special compound EVI-1 acc. VDE-AR-E 2283-5  
 Halogen-free, outer sheath made of PUR in compliance with the normative compound EVM-1 acc. VDE-AR-E 2283-5  
 Colour of the outer sheath: Orange similar to RAL 2003, further sheath colours on request

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC002884 ETIM 5.0 Class-Description: Accessories E-Mobility
Classification ETIM 6:	ETIM 6.0 Class-ID: EC002884 ETIM 6.0 Class-Description: Accessories E-Mobility
Core identification code:	Power cores: colour-coded according to HD 308/VDE 0293-308 Control/ Pilot core: Red
Conductor stranding:	Fine-wired/ Finely stranded according to IEC 60228, conductor class 5 Bare copper
Minimum bending radius:	10 x outer diameter
Nominal voltage:	U <sub>0</sub> /U = 450/750 V AC
Test voltage:	At the core: 2.5 kV AC At the finished cable: 3 kV AC
Protective conductor:	Always with protective conductor (PE), hence uppercase "G" as part of the dimension abbreviation
Temperature range:	-25 °C to +80 °C Maximum permissible conductor temperature: +90 °C

## ÖLFLEX® CHARGE

**Note**

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**ÖLFLEX® CHARGE**

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
74880550	3G2,5+1X0,5	10.1	76.8	155
74880558	3G6+1X0,5	13.2	178	330
74880574	5G2,5+1X0,5	12.8	125	260
74880582	5G6+1X0,5	16	293	460

Last Update (29.06.2018)

©2018 Lapp Group - Technical changes reserved

 Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16