

ÖLFLEX® SERVO 2YSLCY-JB

EMC-optimised motor cable, low-capacitance, double shielded

ÖLFLEX® SERVO 2YSLCY-JB - connection cable for electrical drives with high power and servo applications, EMC-optimised and double shielded.

Info

EMC-optimised design

4-core design in transparent and black

3+3 symmetry reduces common-mode interferences



Interference signals

Benefits

EMC-compliant installation of speed-controlled electrical drives compliant with EN 61800-3

High power transmission for large drives

Longer cable connection possible between frequency converter and motor due to low capacitance design

Ground-symmetrical 3+3 version supports the reduction of bearing currents

Versions with black outer sheath are suitable for outdoor use

Application range

Connecting cable between frequency converter and motor

In dry, damp or wet interiors

Paper industry

Chemical industry

Heavy industry

Product features

Flame-retardant according IEC 60332-1-2

Last Update (24.11.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® SERVO 2YSLCY-JB

Norm references / Approvals

Based on VDE 0207 / 0250 / 0295

Product Make-up

Fine-wire, bare copper conductor

Core insulation: PE

Cores twisted concentrically (protective conductor is symmetrically divided into three parts for the 3+3 version and is split between the power cores in terms of the interstice filler)

Screening: Aluminium-laminated foil wrapping combined with tin-plated copper braiding

4-core version: Optional transparent or black PVC outer sheath

3+3 core version: PVC outer sheath, black – flexible at low temperatures

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000057 ETIM 5.0 Class-Description: Low voltage power cable
Core identification code:	Coloured according to HD 308 S2 VDE 0293-308
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U_0/U : 600/1000 V
Test voltage:	Core/Core: 4 kV Core/Shield: 4 kV
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor Protective conductor of 3+3 version is split between the power cores in terms of the interstice filler
Temperature range:	Flexing: -5°C to +70°C 3+3 core version: -15°C to +70°C Fixed installation: -40°C to +70°C

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging: Ring \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred packaging (e.g. 1 x 500 m drum or 5 x 100 m rings)

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**ÖLFLEX® SERVO 2YSLCY-JB**

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SERVO 2YSLCY-JB / 4-core version - transparent outer sheath				
0036425	4 G 1.5	11.4	95	230
0036426	4 G 2.5	12.4	150	300
0036427	4 G 4	15.6	235	485
0036428	4 G 6	17	320	630
0036429	4 G 10	19.6	533	860
0036430	4 G 16	22.1	789	1290
0036431	4 G 25	26.3	1236	1860
0036432	4 G 35	29.5	1662	2610
0036433	4 G 50	35.8	2345	2950
0036434	4 G 70	40.3	3196	3950
0036435	4 G 95	46.5	4316	5300
0036436	4 G 120	53.2	5435	6600
0036437	4 G 150	57.3	6394	7043
0036438	4 G 185	62.3	7639	8384
ÖLFLEX® SERVO 2YSLCY-JB BK / 4-core version - black outer sheath				
1136450	4 G 1.5	11.4	95	230
1136451	4 G 2.5	12.4	150	300
1136452	4 G 4	15.6	235	485
1136453	4 G 6	17	320	630
1136454	4 G 10	19.6	533	860
1136455	4 G 16	22.1	789	1290
1136456	4 G 25	26.3	1236	1860
1136457	4 G 35	29.5	1662	2610
1136458	4 G 50	35.8	2345	2950
1136459	4 G 70	40.3	3196	3950
1136460	4 G 95	46.5	4316	5300
1136461	4 G 120	53.2	5435	6600
1136462	4 G 150	57.3	6394	7043
1136463	4 G 185	62.3	7639	8384
ÖLFLEX® SERVO 2YSLCYK-JB / 3+3 core version - black outer sheath, flexible at cold temperatures				
0036439	3 X 1,5 + 3 G 0,25	11.4	88	140
0036440	3 X 2,5 + 3 G 0,5	12.2	144	220
0036441	3 X 4 + 3 G 0,75	14.4	224	323

Last Update (24.11.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16

**ÖLFLEX® SERVO 2YSLCY-JB**

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0036442	3 X 6 + 3 G 1,0	15.7	276	420
0036443	3 X 10 + 3 G 1,5	18	491	615
0036444	3 X 16 + 3 G 2,5	20.2	723	819
0036445	3 X 25 + 3 G 4	23.8	1136	1325
0036446	3 X 35 + 3 G 6	26.9	1535	1718
0036447	3 X 50 + 3 G 10	32.6	2156	2399
0036448	3 X 70 + 3 G 10	36.4	2871	3056
0036449	3 X 95 + 3 G 16	42	3953	4162
0036450	3 X 120 + 3 G 16	47.8	4836	5074
0036451	3 X 150 + 3 G 25	51.6	5412	6128
0036479	3 X 185 + 3 G 35	56.5	7041	7500
0036453	3 X 240 + 3 G 50	65.1	8986	9770

Last Update (24.11.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16