

FL BT EPA 2 - Wireless module



1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bluetooth/Ethernet wireless module, 2.1+EDR/4.0, PAN P2P, internal antenna, IP65, 9 V DC ...
30 V DC, M12 connection, WEB, AT-commands and mode button

Your advantages

- Bluetooth wireless modul
- Protocol-transparent communication on Layer 2
- Degree of protection IP65
- Integrated antenna

Commercial data

Item number	1005869
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN2B1
Product key	DNN2B1
Catalog page	Page 375 (C-6-2019)
GTIN	4055626476087
Weight per piece (including packing)	152.6 g
Weight per piece (excluding packing)	105 g
Customs tariff number	85176200
Country of origin	SE

Technical data

Product properties

Type	Stand-Alone
Product type	Wireless module
Application	Ethernet

Wireless card

Number	1
Assembly instructions	Permanently installed

Electrical properties

Maximum power dissipation for nominal condition	1.7 W
---	-------

Supply: Module electronics

Connection technology	M12 connector
Connection method	M12 connector (A-coded, male)
Supply voltage	24 V DC
Supply voltage range	9 V DC ... 30 V DC
Supply current	typ. 36 mA (at 24 V DC)
Current consumption	max. 190 mA (at 9 V DC)

Input data

Digital

Number of inputs	1
------------------	---

Connection data

Power supply input

Connection method	M12 connector (A-coded, male)
-------------------	-------------------------------

Interfaces

Ethernet

Interface	Ethernet
Number	1
Connection method	M12 connectors (D-coded, female)

Functions

Configuration	Web interface, MODE button, AT commands (TCP/IP), SSC
Security	PIN
	Non-discoverable
Wireless licenses	Europe, USA, Canada, additional countries in the e-shop
	RED (Radio Equipment Directive)
	FCC 47 CFR part 15, subpart B
	Belgium

FL BT EPA 2 - Wireless module



1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Country support	Bulgaria
	Denmark
	Germany
	Estonia
	Finland
	France
	Greece
	Great Britain
	Ireland
	Iceland
	Italy
	Canada
	Croatia
	Latvia
	Liechtenstein
	Lithuania
	Luxembourg
	Malta
	Netherlands
	Norway
	Austria
	Poland
	Portugal
	Romania
	Sweden
	Switzerland
	Slovakia
	Slovenia
	Spain
	Czech Republic
Hungary	
USA	
Cyprus (rep.)	
Japan	
Cyprus (rep.)	

10/100 Mbps Ethernet

Number of interfaces	1
Connection method	M12 connectors (D-coded, female)
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100 Mbps
Transmission physics	Copper
Transmission length	100 m (per segment)

Wireless

FL BT EPA 2 - Wireless module



1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Designation	Bluetooth
Antenna connection method	(Internal)
Frequency range	2.402 GHz ... 2.48 GHz (Bluetooth)
Frequency band	2.4 GHz
Wireless standard	Bluetooth 2.1 + EDR
Transmission power	max. 10 dBm
Number of wireless interfaces	1 Bluetooth 2.1+EDR, Bluetooth LE 4.0
Wireless modules that can be connected	1
Profiles supported	PAN (NAP, PANU) GATT (central)

Dimensions

Width	67.8 mm
Height	92.7 mm
Depth	33.2 mm
Note on dimensions	Without M12 connections

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 93 % (non-condensing)
Permissible humidity (storage/transport)	non-condensing

EMC data

Electrostatic discharge

Standards/regulations	EN 61000-4-2
-----------------------	--------------

Electromagnetic HF field

Standards/regulations	EN 61000-4-3
-----------------------	--------------

Fast transients (burst)

Standards/regulations	EN 61000-4-4
-----------------------	--------------

Surge current load (surge)

Standards/regulations	EN 61000-4-5
-----------------------	--------------

Conducted interference

Standards/regulations	EN 61000-4-6
-----------------------	--------------

Emitted interference

Standards/regulations	EN 55022
-----------------------	----------

Mounting

Mounting type	Wall mounting
---------------	---------------

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



Assembly instructions

Internal antenna

1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1005869>



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 196811



UL Listed

Approval ID: FILE E 196811



UL Listed

Approval ID: FILE E 196811



cUL Listed

Approval ID: FILE E 196811

cULus Listed

cULus Listed

FL BT EPA 2 - Wireless module



1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Classifications

ECLASS

ECLASS-11.0	19170101
ECLASS-12.0	19170101
ECLASS-13.0	19170101

ETIM

ETIM 8.0	EC000515
----------	----------

UNSPSC

UNSPSC 21.0	43201400
-------------	----------

FL BT EPA 2 - Wireless module



1005869

<https://www.phoenixcontact.com/gb/products/1005869>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



Accessories

FL EPA RMS - DIN rail adapter

2701133

<https://www.phoenixcontact.com/gb/products/2701133>

Set for mounting devices with EPA design on a DIN rail



FL EPA WMS - Mounting adapter

2701134

<https://www.phoenixcontact.com/gb/products/2701134>

Set for mounting devices with EPA design to wall or mast, including mast clips for a diameter of 25 - 85 mm, can be moved on two axes for optimum alignment, stainless steel



FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



VS-08-RJ45-5-Q/IP20 - RJ45 connector

1656725

<https://www.phoenixcontact.com/gb/products/1656725>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet

SAC-4P-M12MSD/ 2,0-931 - Bus system cable

1569391

<https://www.phoenixcontact.com/gb/products/1569391>



Bus system cable, Ethernet CAT5 (100 Mbps), 4-position halogen-free, shielded, Plug straight M12, coding: D, on free cable end, cable length: 2 m

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



SAC-4P-M12MSD/ 5,0-931 - Bus system cable

1569401

<https://www.phoenixcontact.com/gb/products/1569401>



Bus system cable, Ethernet CAT5 (100 Mbps), 4-position halogen-free, shielded, Plug straight M12, coding: D, on free cable end, cable length: 5 m

NBC-M12MSD/ 1,0-93E/R4AC - Network cable

1407360

<https://www.phoenixcontact.com/gb/products/1407360>



Network cable, Ethernet CAT5 (100 Mbps), 4-position, shielded (Advanced Shielding Technology), Plug straight M12, coding: D / IP67, on Plug straight RJ45 / IP20, cable length: 1 m

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



NBC-M12MSD/ 2,0-93E/R4AC - Network cable

1407361

<https://www.phoenixcontact.com/gb/products/1407361>



Network cable, Ethernet CAT5 (100 Mbps), 4-position, shielded (Advanced Shielding Technology), Plug straight M12, coding: D / IP67, on Plug straight RJ45 / IP20, cable length: 2 m

NBC-M12MSD/ 5,0-93E/R4AC - Network cable

1407362

<https://www.phoenixcontact.com/gb/products/1407362>



Network cable, Ethernet CAT5 (100 Mbps), 4-position, shielded (Advanced Shielding Technology), Plug straight M12, coding: D / IP67, on Plug straight RJ45 / IP20, cable length: 5 m

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



SAC-4P- 2,0-PUR/M12FS - Sensor/actuator cable

1533576

<https://www.phoenixcontact.com/gb/products/1533576>



Sensor/actuator cable, 4-position halogen-free, free cable end, on Socket straight M12, coding: A, cable length: 2 m

SAC-4P- 3,0-PUR/M12FS - Sensor/actuator cable

1668111

<https://www.phoenixcontact.com/gb/products/1668111>



Sensor/actuator cable, 4-position halogen-free, free cable end, on Socket straight M12, coding: A, cable length: 3 m

FL BT EPA 2 - Wireless module

1005869

<https://www.phoenixcontact.com/gb/products/1005869>



SAC-4P- 5,0-PUR/M12FS - Sensor/actuator cable

1668124

<https://www.phoenixcontact.com/gb/products/1668124>



Sensor/actuator cable, 4-position halogen-free, free cable end, on Socket straight M12, coding: A, cable length: 5 m

SAC-4P-10,0-PUR/M12FS - Sensor/actuator cable

1683002

<https://www.phoenixcontact.com/gb/products/1683002>



Sensor/actuator cable, 4-position halogen-free, free cable end, on Socket straight M12, coding: A, cable length: 10 m

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk