

FL SWITCH EP7400-M8GSFP - Communication module



1144383

<https://www.phoenixcontact.com/gb/products/1144383>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Extension module, provides eight SFP at 100/1000 Mbps



Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1144383 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DNN125 |
| Product key | DNN511 |
| GTIN | 4063151132125 |
| Weight per piece (including packing) | 642.2 g |
| Weight per piece (excluding packing) | 630.2 g |
| Country of origin | CA |

FL SWITCH EP7400-M8GSFP - Communication module



1144383

<https://www.phoenixcontact.com/gb/products/1144383>

Technical data

Product properties

| | |
|----------------|-----------------------|
| Product type | Extension module |
| Product family | Managed Switch EP7000 |

System properties

Functionality

| | |
|-----------------|---|
| Basic functions | Media module for modular managed switch |
|-----------------|---|

Interfaces

Ethernet

| | |
|--------------------|---------------|
| Connection method | SFP |
| Transmission speed | 100/1000 Mbps |
| No. of channels | 8 (SFP ports) |
| Transmission speed | 100/1000 Mbps |

Environmental and real-life conditions

Ambient conditions

| | |
|--|--|
| Degree of protection | IP20 |
| Ambient temperature (operation) | -40 °C ... 85 °C (Type tested to 85 °C for 16 hours) |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |
| Permissible humidity (operation) | 10 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 10 % ... 95 % (non-condensing) |

Standards and regulations

| | |
|--------------------------|--------------------|
| Standard designation | Ambient conditions |
| Standards/specifications | IEC 61850-3 |
| | IEEE 1613 |

Mounting

| | |
|---------------|---------------------------------|
| Mounting type | Internal module for rack switch |
|---------------|---------------------------------|

FL SWITCH EP7400-M8GSFP - Communication module



1144383

<https://www.phoenixcontact.com/gb/products/1144383>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1144383>



EAC

Approval ID: RU D-DE.GB09.B.00312

FL SWITCH EP7400-M8GSFP - Communication module



1144383

<https://www.phoenixcontact.com/gb/products/1144383>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 19170407 |
| ECLASS-12.0 | 19170407 |
| ECLASS-13.0 | 19170401 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000309 |
|----------|----------|

FL SWITCH EP7400-M8GSFP - Communication module



1144383

<https://www.phoenixcontact.com/gb/products/1144383>

Environmental product compliance

EU RoHS

| | |
|---|-----------------------------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 6(c), 7(a), 7(c)-I, 7(c)-II |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|---|
| REACH candidate substance (CAS No.) | 1-Methyl-2-pyrrolidone (NMP)(CAS: 872-50-4) |
| | N,N-dimethylacetamide(CAS: 127-19-5) |
| | Hexahydromethylphthalic anhydride(CAS: n/a) |
| | Lead titanium zirconium oxide(CAS: 12626-81-2) |
| | 4,4'-isopropylidenediphenol(CAS: 80-05-7) |
| | Terphenyl, hydrogenated(CAS: 61788-32-7) |
| | Lead(CAS: 7439-92-1) |
| | 2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one(CAS: 71868-10-5) |

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk