

1283116

https://www.phoenixcontact.com/gb/products/1283116

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement battery, VRLA-AGM, 2x12 V DC, 4 Ah. Only for 1274117 UPS-BAT/PB/24DC/4AH, 2320267 QUINT-UPS/24DC/24DC/10/3.4AH from V/C 06, 2905908 TRIO-UPS-2G/1AC/1AC/120V/750VA, and 2905909 TRIO-UPS-2G/1AC/1AC/230V/750VA

## Commercial data

Item number	1283116
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CMUEV3
Product key	CMUEV3
GTIN	4063151487676
Weight per piece (including packing)	2,950 g
Weight per piece (excluding packing)	2,950 g
Customs tariff number	85072080
Country of origin	CN



1283116

https://www.phoenixcontact.com/gb/products/1283116

# Technical data

### Notes

General	
Note on the battery	This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the technical data area under "Latest startup".

### Energy storage

Input	
Input voltage	2x 12 V
Nominal capacity	4 Ah

#### General

General	
Battery type	BB Battery HR4.2-12FR
Battery technology	VRLA-AGM
IQ-Technology	no
Latest startup date (battery only)	6 Months (0 °C 20 °C)
Latest startup (battery only) - range	3 Months 6 Months (20 °C 30 °C)
	1 Months 3 Months (30 °C 40 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)

### **Product properties**

Product type	Battery (not rechargeable)
Product family	Replacement battery
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
Insulation characteristics	
Protection class	Ш

### Dimensions

Item dimensions

Width	82 mm
Height	142 mm
Depth	102 mm

### Environmental and real-life conditions



1283116

https://www.phoenixcontact.com/gb/products/1283116

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C 40 °C
Ambient temperature (charge)	0 °C 40 °C
Ambient temperature (discharge)	-20 °C 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

### Ex data

Suited for EX-applications	No
----------------------------	----



1283116

https://www.phoenixcontact.com/gb/products/1283116

## Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1283116



EAC Approval ID: RU\*DE\*01.B.78948/21



1283116

https://www.phoenixcontact.com/gb/products/1283116

## Classifications

## ECLASS

	ECLASS-11.0	27059090
	ECLASS-12.0	27059090
	ECLASS-13.0	27059090
ET	IM	
	ETIM 9.0	EC011878
UN	ISPSC	
	UNSPSC 21.0	26111700



1283116

https://www.phoenixcontact.com/gb/products/1283116

# Environmental product compliance

#### EU RoHS

Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE EFUP-8
An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
Lead(CAS: 7439-92-1)

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk