

1283119

https://www.phoenixcontact.com/gb/products/1283119

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement battery, VRLA-AGM, 2x12 V DC, 7 Ah

#### Commercial data

Item number	1283119
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CMUEV3
Product key	CMUEV3
GTIN	4063151486891
Weight per piece (including packing)	5,252.6 g
Weight per piece (excluding packing)	5,253 g
Customs tariff number	85072080
Country of origin	CN



1283119

https://www.phoenixcontact.com/gb/products/1283119

#### Technical data

#### Notes

$\overline{}$	_		_	
l٦	e	n	e	ra

Note on the battery  This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the technical data area under "Latest startup".

#### Energy storage

#### Input

Input voltage	2x 12 V
Nominal capacity	7 Ah

#### General

Battery type	BB Battery BP7-12FR
Battery technology	VRLA-AGM
IQ-Technology	no
Latest startup date (battery only)	12 Months (0 °C 20 °C)
Latest startup (battery only) - range	9 Months 12 Months (20 °C 30 °C)
	6 Months 9 Months (30 °C 40 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)

#### Product properties

Product type	Battery (not rechargeable)
Product family	Replacement battery
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
Insulation characteristics	
Protection class	III

2

#### Dimensions

#### Item dimensions

Degree of pollution

Width	134 mm
Height	153 mm
Depth	100 mm

#### Environmental and real-life conditions



1283119

https://www.phoenixcontact.com/gb/products/1283119

#### Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C 40 °C
Ambient temperature (charge)	0 °C 40 °C
Ambient temperature (discharge)	-20 °C 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

#### Ex data

Suited for EX-applications	No



1283119

https://www.phoenixcontact.com/gb/products/1283119

### Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1283119



#### **GOST-R**

Approval ID: ROSS DE.BL08.D00191



1283119

https://www.phoenixcontact.com/gb/products/1283119

### Classifications

#### **ECLASS**

202.00					
	ECLASS-11.0	27059090			
	ECLASS-12.0	27059090			
	ECLASS-13.0	27059090			
ΕΊ	ETIM				
	ETIM 9.0	EC011878			
U	UNSPSC				
	UNSPSC 21.0	26111700			



1283119

https://www.phoenixcontact.com/gb/products/1283119

### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE
China RoHS	
Environment friendly use period (EFUP)	EFUP-8
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk