

# FL SWITCH EP6512-4GSFP-HV - Industrial Ethernet Switch



1539368

<https://www.phoenixcontact.com/gb/products/1539368>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Security-enabled managed switch with eight RJ45 ports at 10/100/1000 Mbps, four SFP ports at 100/1000 Mbps and operating temperature of -40 ... +85°C, 100-240 V AC/DC (Nom.) power supply

## Product description

FL SWITCH EP64... advanced managed network switches provide an adaptable platform to meet the electric power industry's increasing requirements for scalable network performance, uptime, and security.

## Your advantages

- Layer 2 and Layer 3 functions
- IEEE 1588 v2 precision timing support
- Support for Access Control Lists (ACL) for traffic filtering, RADIUS, and TACAC's authentication.

## Commercial data

Item number	1539368
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNN512
Product key	DNN512
GTIN	4067923011458
Weight per piece (including packing)	2,612 g
Weight per piece (excluding packing)	2,005 g
Customs tariff number	85176200
Country of origin	CA

# FL SWITCH EP6512-4GSFP-HV - Industrial Ethernet Switch



1539368

<https://www.phoenixcontact.com/gb/products/1539368>

## Technical data

### Dimensions

Width	82.7 mm
Height	188.39 mm
Depth	197.12 mm

### Interfaces

#### Ethernet

Connection method	RJ45
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100/1000 Mbps
Transmission physics	Copper
Transmission length	100 m (per segment)

#### Ethernet (SFP)

Connection method	SFP
Transmission speed	100/1000 Mbps (full duplex)
Transmission physics	Depending on the SFP module

### Output data

#### Digital:

Output name	Alarm relay output: 24 V DC, 1 A maximum
-------------	--

### Product properties

Product type	Switch
Product family	Managed Switch EP6000

#### Insulation characteristics

Overvoltage category	II
Degree of pollution	2

#### Switch functions

Signal contact control voltage	24 V DC
Signal contact control current	1 A
MAC address table	16k

### Electrical properties

#### Supply

Supply voltage range	100 V AC/DC ... 240 V AC/DC
----------------------	-----------------------------

#### Function

Signal contact control voltage	24 V DC
Signal contact control current	1 A

# FL SWITCH EP6512-4GSFP-HV - Industrial Ethernet Switch



1539368

<https://www.phoenixcontact.com/gb/products/1539368>

## Connection data

Connection method	Screw connection
-------------------	------------------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C (Type tested to 85 °C for 16 hours)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	10 % ... 95 % (non-condensing)

## Standards and regulations

Standard designation	Ambient conditions
Standards/specifications	IEC 61850-3
	IEEE 1613

## Approvals

### Conformity/Approvals

Conformance	CE-compliant
-------------	--------------

## EMC data

Noise immunity	IEC 61850-3, IEEE 1613, EN 61000-6-2: 2005
----------------	--

# FL SWITCH EP6512-4GSFP-HV - Industrial Ethernet Switch



1539368

<https://www.phoenixcontact.com/gb/products/1539368>

## Classifications

### ECLASS

ECLASS-11.0	19170401
ECLASS-13.0	19170401

# FL SWITCH EP6512-4GSFP-HV - Industrial Ethernet Switch



1539368

<https://www.phoenixcontact.com/gb/products/1539368>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c), 7(a), 7(c)-I, 7(c)-II

### China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

### EU REACH SVHC

REACH candidate substance (CAS No.)	1-Methyl-2-pyrrolidone (NMP)(CAS: 872-50-4)
	N,N-dimethylacetamide(CAS: 127-19-5)
	1, 2-dimethoxyethane; ethylene glycol dimethyl ether (EGDME)(CAS: 110-71-4)
	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead titanium zirconium oxide(CAS: 12626-81-2)
	Lead titanium trioxide(CAS: 12060-00-3)
	4,4'-isopropylidenediphenol(CAS: 80-05-7)
	Terphenyl, hydrogenated(CAS: 61788-32-7)
	Lead(CAS: 7439-92-1)
	2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one(CAS: 71868-10-5)

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)