

https://www.phoenixcontact.com/gb/products/2703015



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Patch panel, two RJ45 jacks, 10/100/1000 MBps, DIN rail adapter, IP20

Product description

Ethernet patch panels enable quick and easy connection between the field cabling and control cabinet cabling. The passive termination panels are a convenient alternative to the on-site assembly of RJ45 connectors.

Your advantages

- 10/100/1000 Mbps, CAT6
- Extended temperature range of -40 °C ... +75 °C
- Shipbuilding approval in accordance with DNV GL
- PoE-capable in accordance with IEEE 802.3bt, type 4

Commercial data

Item number	2703015
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DNC334
Product key	DNC334
Catalog page	Page 360 (C-6-2019)
GTIN	4055626462868
Weight per piece (including packing)	111.3 g
Weight per piece (excluding packing)	57.63 g
Customs tariff number	85366990
Country of origin	DE



https://www.phoenixcontact.com/gb/products/2703015



Technical data

Notes

14:1	1:	4:~~		iction
JTII	แฮล	tion.	restr	ICTION

CCCex note Use	e in potentially explosive areas is not permitted in China.
----------------	---

Product properties

Product type	Patch panel
MTTF	105699 Years
Insulation characteristics	
Overvoltage category	II II

Electrical properties

Maximum power dissipation for nominal condition	0 W (passive module, no supply voltage required)
Rated insulation voltage	85 V DC (In accordance with EN/IEC 60079-7, Annex H)

Interfaces


Data: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3

Serial transmission speed	10/100/1000 Mbps
Frequency range	250 MHz
Connection method	RJ45 jack
Pin assignment	1:1
Transmission length	100 m (including patch cables)
Transmission medium	Copper
Output nominal voltage	< 57 V DC
Maximum output power	60 W
Maximum output current	725 mA (Per channel)

Data: Ethernet interface, 10/100/1000Base-T(X) in accordance with IEEE 802.3

Connection method RJ45 jack

Dimensions





https://www.phoenixcontact.com/gb/products/2703015



Height	101.3 mm
Depth	50 mm
aterial specifications	
Material	Plastic
Flammability rating according to UL 94	V0
nvironmental and real-life conditions	
Ambient conditions	
Degree of protection	IP20 (Manufacturer's declaration)
Ambient temperature (operation)	-40 °C 75 °C
Ambient temperature (storage/transport)	-40 °C 85 °C
Altitude	≤ 5000 m (For restrictions, see the manufacturer's declaration for altitude operation)
	≤ 2000 m (Restrictions for ATEX applications)
Permissible humidity (operation)	10 % 95 % (non-condensing)
CE	CE compliant
Certificate	CE-compliant
ATEX	
Identification	
Certificate	PxCIF18ATEX2703015U
Note	Please follow the special installation instructions in the documentation!
UKEX	
Identification	
Certificate	PxCIMA22UKEX2703015U
UL, USA	
Certificate	UL 60079-0 Ed. 6 / UL 60079-15 Ed. 4
UL, Canada	
Certificate	CSA 22.2 No. 60079-0 Ed. 3 / CSA 22.2 No. 60079-15:16
Corrosive gas test	
Identification	ISA-S71.04-1985 G3 Harsh Group A
Shipbuilding	
Identification	DNV GL
DNV GL data	
Temperature	D
Humidity	В
Vibration	В



https://www.phoenixcontact.com/gb/products/2703015



	EMC	В
Mounting		
	Mounting type	DIN rail mounting, stationary
	Assembly instructions	The product can be snapped onto all 35 mm DIN rails in accordance with EN 60715.


2703015


https://www.phoenixcontact.com/gb/products/2703015



Drawings


Schematic diagram






Removal

Schematic diagram






Mounting on a DIN rail




https://www.phoenixcontact.com/gb/products/2703015



Dimensional drawing






Compact housing

2703015

https://www.phoenixcontact.com/gb/products/2703015



Schematic diagram



Front view



https://www.phoenixcontact.com/gb/products/2703015



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/2703015



DNV GL

Approval ID: TAA00001KR



UL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 238705



cUL Listed

Approval ID: FILE E 366272



UL Listed

Approval ID: FILE E 366272

cULus Listed

cULus Listed



https://www.phoenixcontact.com/gb/products/2703015



Classifications

ECLASS

	ECLASS-11.0	19170112
	ECLASS-12.0	19170112
	ECLASS-13.0	19170112
ET	TIM	
	ETIM 8.0	EC002697

UNSPSC

UNSPSC 21.0 432233	00
--------------------	----



https://www.phoenixcontact.com/gb/products/2703015



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/gb/products/2703015



Accessories

PP-RJ-RJ-F - Patch panels

2703020

https://www.phoenixcontact.com/gb/products/2703020



Patch panel, two RJ45 jacks, 10/100/1000 MBps, DIN rail adapter, IP20, shield current monitoring, surge protection

PP-RJ-SC-F - Patch panels

2703021

https://www.phoenixcontact.com/gb/products/2703021



Patch panel, RJ45 jack on screw terminal blocks, 10/100/1000 Mbps, DIN rail adapter, IP20, shield contacting with strain relief, shield current monitoring, surge protection



https://www.phoenixcontact.com/gb/products/2703015



PP-RJ-SCC-F - Patch panels

2703022

https://www.phoenixcontact.com/gb/products/2703022



Patch panel, RJ45 jack on Push-in terminal blocks, 10/100/1000 Mbps, DIN rail adapter, IP20, shield contacting with strain relief, shield current monitoring, surge protection

PP-RJ-IDC-F - Patch panels

2703023

https://www.phoenixcontact.com/gb/products/2703023



Patch panel, RJ45 jack on IDC terminal blocks, 10/100/1000 Mbps, DIN rail adapter, IP20, shield contacting with strain relief, shield current monitoring, surge protection



https://www.phoenixcontact.com/gb/products/2703015



FL CRIMPTOOL - Assembly tool

2744869

https://www.phoenixcontact.com/gb/products/2744869

Crimping pliers, for assembling the RJ45 plugs FL PLUG RJ45..., for assembly on site



FL ISOLATOR 100-RJ/RJ - Network isolator

2313931

https://www.phoenixcontact.com/gb/products/2313931



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Possible to connect two RJ45 plugs.



https://www.phoenixcontact.com/gb/products/2703015



FL ISOLATOR 1000-RJ/RJ - Network isolator

2313915

https://www.phoenixcontact.com/gb/products/2313915



Passive network isolator for electrical isolation in Ethernet networks. This protects Ethernet devices from potential differences of up to 4 kV. Can be used for transmission speeds of up to 1 Gbps. Possible to connect two RJ45 plugs.

FL ISOLATOR 100-M12 - Network isolator

2902985

https://www.phoenixcontact.com/gb/products/2902985



Passive network isolator for electrical isolation in Ethernet networks. For the protection of Ethernet devices against potential differences of up to 4 kV. Can be used for transmission speeds of up to 100 Mbps. Ethernet connection via two M12 sockets (D-coded).



https://www.phoenixcontact.com/gb/products/2703015



NBC-R4AC-R4AC-IE8A/.../... - Patch cable

1411854

https://www.phoenixcontact.com/gb/products/1411854



Patch cable, degree of protection: IP20, number of positions: 8, 10 Gbps, ${\rm CAT6}_{\rm A}$, cable outlet: straight, Ethernet

NBC-R4AC/10G-R4AC/10G-94F/2,0 - Patch cable

1408360

https://www.phoenixcontact.com/gb/products/1408360



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 2.0 m



https://www.phoenixcontact.com/gb/products/2703015



NBC-R4AC/10G-R4AC/10G-94F/3,0 - Patch cable

1408365

https://www.phoenixcontact.com/gb/products/1408365



Patch cable, CAT6 $_{\rm A}$, 4-pair, shielded, connection not crossed (line), assembled at both ends with RJ45/IP20 connectors, outer sheath material: PUR, length: 3.0 $_{\rm m}$

NBC-R4AC/1,0-93B/R4AC - Patch cable

1408968

https://www.phoenixcontact.com/gb/products/1408968



Patch cable, degree of protection: IP20, cable length: 1 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET



https://www.phoenixcontact.com/gb/products/2703015



NBC-R4AC/2,0-93B/R4AC - Patch cable

1408969

https://www.phoenixcontact.com/gb/products/1408969



Patch cable, degree of protection: IP20, cable length: 2 m, number of positions: 4, 100 Mbps, CAT5, material: PA 6.6, PROFINET

FL CAT5 PATCH 0,3 - Patch cable

2832250

https://www.phoenixcontact.com/gb/products/2832250



Patch cable, CAT5, assembled, 0.3 m



https://www.phoenixcontact.com/gb/products/2703015



FL CAT5 PATCH 0,5 - Patch cable

2832263

https://www.phoenixcontact.com/gb/products/2832263



Patch cable, CAT5, assembled, 0.5 m

FL CAT5 PATCH 1,0 - Patch cable

2832276

https://www.phoenixcontact.com/gb/products/2832276



Patch cable, CAT5, assembled, 1 m



https://www.phoenixcontact.com/gb/products/2703015



FL CAT5 PATCH 1,5 - Patch cable

2832221

https://www.phoenixcontact.com/gb/products/2832221



Patch cable, CAT5, assembled, 1.5 m

FL CAT5 PATCH 2,0 - Patch cable

2832289

https://www.phoenixcontact.com/gb/products/2832289



Patch cable, CAT5, assembled, 2 m



https://www.phoenixcontact.com/gb/products/2703015



FL CAT5 PATCH 3,0 - Patch cable

2832292

https://www.phoenixcontact.com/gb/products/2832292



Patch cable, CAT5, assembled, 3 m

VS-08-RJ45-10G/Q - RJ45 connector

1419001

https://www.phoenixcontact.com/gb/products/1419001



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: black, Ethernet



https://www.phoenixcontact.com/gb/products/2703015



VS-PN-RJ45-5-Q/IP20 - RJ45 connector

1658435

https://www.phoenixcontact.com/gb/products/1658435



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 4, 100 Mbps, CAT5, material: Plastic, connection method: Insulation displacement connection, cable outlet: straight, color: traffic grey A RAL 7042, PROFINET

VS-CABLE-STRIP-VARIO - Stripping tool

1657407

https://www.phoenixcontact.com/gb/products/1657407

Stripping tool, for the multi-level stripping of shielded cables





https://www.phoenixcontact.com/gb/products/2703015



VS-08-RJ45-5-Q/IP20 - RJ45 connector

1656725

https://www.phoenixcontact.com/gb/products/1656725



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: traffic grey A RAL 7042, Ethernet

VS-08-RJ45-5-Q/IP20 BK - RJ45 connector

1658008

https://www.phoenixcontact.com/gb/products/1658008



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 23, cable outlet: straight, color: black, Ethernet



https://www.phoenixcontact.com/gb/products/2703015



SZF 0-0,4X2,5 - Screwdriver

1204504

https://www.phoenixcontact.com/gb/products/1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: $0.4 \times 2.5 \times 75$ mm, 2-component grip, with non-slip grip

MICROFOX-SP - Diagonal cutter

1212488

https://www.phoenixcontact.com/gb/products/1212488



Electronic diagonal cutter, tapered head, angled (21°), without chamfer, with opening spring



https://www.phoenixcontact.com/gb/products/2703015



VS-OE-OE-94F/... - Data cable

1417359

https://www.phoenixcontact.com/gb/products/1417359



Data cable, Ethernet CAT6 $_{\rm A}$ (10 Gbps), 8-position halogen-free, shielded, free cable end, on free cable end, cable length: Free entry (0.5 ... 400 m)

FL-PP-RJ45-SC - Patch panels

2901643

https://www.phoenixcontact.com/gb/products/2901643



Patch panel, one RJ45 jack to 8 screw connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers



https://www.phoenixcontact.com/gb/products/2703015



FL-PP-RJ45-LSA - Patch panels

2901645

https://www.phoenixcontact.com/gb/products/2901645



Patch panel, one RJ45 jack to 8 LSA connection terminal blocks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via bridges

FL-PP-RJ45/RJ45 - Patch panels

2901646

https://www.phoenixcontact.com/gb/products/2901646



Patch panel, two RJ45 jacks (1:1 assignment), CAT5e, 10/100/1000 Mbps, DIN rail adapter, IP20, option of shield contacting to the DIN rail via jumpers

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk