

### Socket outlet Type 2 IP54 up to 63A with cover and connector locking

Socket outlet Type 2 IP54 up to 63A with cover and connector locking, For installation in charging stations

#### Info

Sturdy and durable socket outlet for frequent connection



UV-resistant



Reliability



Robust



Oil-resistant



Assembly time



Mechanical resistance



Corrosion-resistant



Good chemical resistance



e-Mobility



Suitable for outdoor use

Last Update (23.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

**Socket outlet Type 2 IP54 up to 63A with cover and connector locking**

Cold-resistant

**Benefits**

Socket outlet and controller fits perfectly together

**Application range**

For installation in charging stations

**Product features**

5 different versions for all installation situations

Socket outlet type 2 according to IEC62196-1,2 and IEC 61851-1

Optionally available: Hinged lid locking, RGB LED, flat design

**Product Make-up**

screw terminals for 3P+N+PE as well as PP and CP

with easy CONTACT and silver plated contacts

Plug interlock with integrated actuator

hinged lid included

**Technical Data**

Classification ETIM 5:

ETIM 5.0 Class-ID: EC002839

ETIM 5.0 Class-Description: Accessories for battery/charger

Nominal voltage:

200/346 V – 240/415 V

Protection rating:

IP 54

Temperature range:

-30°C up to +50°C

**Note**

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**Socket outlet Type 2 IP54 up to 63A with cover and connector locking**

Article number	Charging current	Article designation
Socket outlet type 2 with hinged lid locking		
74880203	≤ 20A	EVCP2 Controller 74880217 or 74880220
74880204	≤ 32A	EVCP2 Controller 74880217 or 74880220
74880205	≤ 63A	EVCP2 Controller 74880217 or 74880220

Last Update (23.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16